

MSD Platinum (Touring/Stage)

MSD Platinum 21 R 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General information		Color Rendering Index (Nom)		-
Cap-Base	- [-]	Operating and electrical		
Operating Position	UNIVERSAL [Any or Universal (U)]	Power (Nom)	470 W	
Main Application	Stage/Touring	Controls and dimming		
Life to 50% Failures (Nom)	1500 h	Dimmable	Yes	
System Description	Reflector-E21.4	Mechanical and housing		
Light technical		Cap-Base Information	-	
Color Code	2	Luminaire design requirements		
Luminous Flux (Nom)	23000 lm	Bulb Temperature (Max)	900 °C	
Chromaticity Coordinate X (Nom)	297			
Chromaticity Coordinate Y (Nom)	300			
Correlated Color Temperature (Nom)	8000 K			

MSD Platinum (Touring/Stage)

Pinch Temperature (Max)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C
Product data	
Full product code	871869667826800
Order product name	MSD Platinum 21 R 1CT/8
EAN/UPC - Product	8718696678268

Order code	928197805314
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	928197805314
Net Weight (Piece)	110.000 g

Dimensional drawing



MSD Platinum 21 R 1CT/8

Product	D (max)	O	C (max)
MSD Platinum 21 R 1CT/8	54.5 mm	1.2 mm	60 mm

Photometric data

